



LBC 3082/00 Fire Dome



During a fire, the ceiling cavity in which loudspeakers are installed can allow flames to spread throughout a building. To prevent fire entering the cavity via the loudspeaker, the ceiling loudspeaker can be fitted with a steel fire dome. This optional fire dome is mounted on the loudspeaker assembly using four self-tapping screws supplied with the fire dome. The fire dome has knockout holes for two grommets (supplied) and two cable glands (PG 13).

This fire dome can only be used with the LBC 3099/41 Ceiling Loudspeaker.

Technical Specifications

Mechanical

Dimensions (dia. x max. depth)	182 x 100 mm (7.2 x 3.9 in)
Weight	540 g (1.19 lb)
Color	Flame red (RAL 3000)

Ordering Information

LBC 3082/00 Fire Dome	LBC 3082/00
metal fire dome for LBC 3099/41 ceiling loudspeaker	

Certifications and Approvals

Region	Certification
Europe	CE
B15	DIN 4102-8

Parts Included

Quantity	Components
1	LBC 3082/00 Fire Dome
4	Self tapping screws
2	Rubber grommets

Americas:

Bosch Communications Systems
12000 Portland Avenue South
Burnsville, Minnesota 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2600
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by