

LBC 3941/11 Sound Projector

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Excellent speech and music reproduction
- ▶ Very wide opening angle
- ▶ Modern unobtrusive styling
- ▶ Simple power setting
- ▶ Splash – waterproof

The LBC 3941/11 is a 6 W cost-effective sound projector. It features a very wide opening angle and unobtrusive styling. Water and dust protection to IP 65 make it suitable for indoor and outdoor use.

Functions

The sound projector features a very wide opening angle (90 degrees) which means fewer units are required to cover a given area. Its wide frequency range also results in better speech and music reproduction, while the directivity ensures that the sound is accurately projected to where it is needed most.

The LBC 3941/11 sound projector is finished in an attractive white color, and its unobtrusive appearance complements today’s interior lighting. The color and styling of the front grille matches an existing Bosch ceiling loudspeaker (LBC 3951/11).

Certifications and Approvals

All Bosch loudspeakers are designed to withstand operating at their rated power for 100 hours in accordance with IEC 268-5 Power Handling Capacity (PHC) standards. Bosch has also developed the Simulated Acoustical Feedback Exposure (SAFE) test to demonstrate that they can withstand two times

their rated power for short durations. This ensures extra reliability under extreme conditions, leading to higher customer satisfaction, longer operating life, and much less chance of failure or performance deterioration.

The enclosures are made from high-impact self-extinguishing ABS (according to class UL 94 V0).


Safety	acc. to EN 60065
Water and dust protection	acc. to EN 60529, IP 65
Self-Extinguishing	acc. to UL 94 V0

Region	Certification
Europe	CE



Installation/Configuration Notes

The sound projector is supplied with a steel mounting bracket painted in white. The bracket has three 10 mm holes, which can be used to easily mount the projector to walls and ceilings. The direction of the projector can be adjusted by means of two screws covered with white plastic covers. The unit is supplied with a 2 m color-coded five-core cable, with each color connected to a different primary tap on the matching


transformer. This makes it easy to select full-power, half-power, quarter-power and eighth-power radiation without opening the unit during installation.




Circuit diagram



Dimensions in mm (in)



Frequency response



- 250 Hz
- - - 500 Hz
- 1000 Hz
- - - 2000 Hz
- 4000 Hz
- - - 8000 Hz

Polar diagram (measured with pink noise)

	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz
SPL 1.1	82	84	83	88	92	88	88
SPL max.	90	92	91	96	100	96	96
Q-factor	1.2	1.2	1.6	2.9	5.1	8.5	18
Efficiency	0.17	0.26	0.16	0.28	0.39	0.09	0.04
H. angle	360	360	360	180	120	90	60
V. angle	360	360	360	180	120	90	60

Acoustical performance specified per octave

Technical Specifications

Electrical*

Maximum power	9 W
Rated power	6 / 3 / 1.5 / 0.75 W
Sound pressure level at 6 W / 1 W (1 kHz, 1 m)	96 dB / 88 dB (SPL)
Sound pressure level at 6 W / 1 W (2 kHz, 1 m)	100 dB / 92 dB (SPL)
Opening angle at 1 kHz / 4 kHz (-6 dB)	180° / 90°
Effective frequency range (-10 dB)	130 Hz to 18 kHz
Rated voltage	100 V

Rated impedance	1667 ohm
Connection	2 m 5-wire cable

* Technical performance data acc. to IEC 60268-5

Mechanical

Dimensions (D x L)	165 x 200 mm (6.50 x 7.87 in)
Speaker diameter	100 mm (4 in)
Weight	1.5 kg (3.3 lb)
Color	White (RAL 9010)
Magnet weight	101 g (3.57 oz)

Environmental

Operating temperature	-25 °C to +55 °C (-13 °F to +131 °F)
Storage temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative humidity	<95%

Ordering Information

LBC 3941/11 Sound Projector

6 W, white ABS

Order number **LBC3941/11**

Represented by:

Americas:

Bosch Communications Systems
12000 Portland Avenue South
Burnsville, Minnesota 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2600
Fax: +65 6571 2698
apr.securitysystems@bosch.com
www.boschsecurity.com